

3M[™] LED Light Vision[™] Series Safety Glasses

Technical datasheet



Product description

The 3M™ LED Light Vision™ premium line spectacles offer excellent protection and the added benefit of integrated lights.

The temple-mounted LED units allow the user to light their field of view whist keeping their hands free for work.

Key features

- ▶ Integrated LED lights with a battery life of up to 50 hours
- ▶ LED lights: 5 7 Lumens per LED
- Design provides excellent coverage and good field of vision
- Optical Class 1 to allow prolonged comfortable wear
- ▶ Inclinable lens for easy adjustment and maximum comfort
- Offers excellent protection against UV radiation
- Lens coatings provide scratch resistance and anti-fogging
- ▶ Weight: 54g

Product range

Product ID	Description	Lens colour	Frame colour
Light Vision	3M [™] Light Vision [™] Safety Glasses with clear PC lens	Clear PC	Silver / Black

Typical applications

These products can be used in a wide range of applications including:

- Construction
- Engineering
- ► General assembly
- ▶ Light duty maintenance and repair

Intended use

These products are intended for protection against high speed particles at low energy (F) at extreme temperature conditions, -5°C and +55°C, (T) in accordance with EN 166:2001.

This product also helps protect against UV radiation in accordance with EN 170:2002.

Clear – Good colour recognition and excellent UV protection

Use limitation

- Never modify or alter this product
- Do not use this product against hazards other than those specified in this document
- In accordance with EN 166:2001 safety spectacles cannot be tested and approved for use against liquid droplets. Where liquid protection is specified a suitable product should be considered, for example safety goggles

Standards and approval

These products are type examined by BSI Group, Notified Body number 2797.

These products are CE marked to the requirements of European Regulation (EU) 2016/425.

The applicable legislation can be determined by reviewing the Certificate and Declaration of Conformity at www.3M.com/Eye/certs

Materials listing

Description	Material
Lens	Polycarbonate
Frame	Nylon
Temple (rigid)	Polycarbonate
Temple tips (flexible)	Styrene Ethylene Butylene Styrene
Soft frame and nose pads	Styrene Ethylene Butylene Styrene
Screws	Plated zinc

Marking

The products have demonstrated compliance with the requirements of EN 166:2001 and associated standards and bear the following marks:

Product ref	Lens marking	Frame marking
Light Vision	2C-1.2 3M 1 FT	3M EN 166 FT CE

Explanation of marking

Marking	Description
2C-1.2 (EN 170:2002)	UV protection. This product conforms to the requirements of the standard, providing UV protection for the complete specified range (210nm – 365nm). Products marked C provide good colour recognition.
5-2.5 (EN 172:1994 as amended)	Sun-glare protection conforming to the requirements of the standard, providing UV protection for the complete specified range (280nm – 350nm).
1	Optical class
F	Impact protection against high speed particle at low energy (45m/s)
Т	Tested for impact protection at extreme temperature conditions -5°C and +55°C

IMPORTANT NOTICE

The use of the 3M product described within this document assumes that the user has previous experience of this type of product and that it will be used by a competent professional. Before any use of this product it is recommended to complete some trials to validate the performance of the product within its expected application.

All information and specification details contained within this document are inherent to this specific 3M product and would not be applied to other products or environment. Any action or usage of this product made in violation of this document is at the risk of the user.

Compliance to the information and specification relative to the 3M product contained within this document does not exempt the user from compliance with additional guidelines (safety rules, procedures). Compliance to operational requirements especially in respect to the environment and usage of tools with this product must be observed. The 3M group (which cannot verify or control those elements) would not be held responsible for the consequences of any violation of these rules which remain external to its decision and control.

Warranty conditions for 3M products are determined with the sales contract documents and with the mandatory and applicable clause, excluding any other warranty or compensation.

For more information on 3M products and services please contact 3M.



3M United Kingdom PLC 3M Centre, Cain Road Bracknell, Berkshire RG12 8HT Tel.: 0870 60 800 60 www.3M.eu/Safety 3M Ireland Limited The Iveagh Building The Park, Carrickmines Dublin 18 t: 1800 320 500

