

Bruxelles - jacket				
Description	<p>wide back zipped pocket, wide breast and bottom pockets, badge pocket loop, tools loop, reinforced elbows, collar polyester CoolDRY® insert, pen pocket, 3M™ Scotchlite™ Reflective Material back reflex inserts - 8910 Silver Fabric, net insert under the armpit, adjustable waist and cuff, loop for headset, arm ergonomic design, mobile phone pocket with E-CARE, YKK® zip.</p> <p>NEW: (04 anthracite/black) badge pocket loop, wide breast and bottom pockets, reinforced elbows, pen pocket, adjustable waist and cuff, net insert under the armpit, collar polyester CoolDRY® insert, loop for headset, arm ergonomic design, mobile phone pocket with E-CARE, YKK® zip, 3M™ Scotchlite™ Reflective Material back reflex inserts - 8910 Silver Fabric</p>			
Maintenance	<p>Maximum wash temperature: 60°C; Do not bleach; Dry clean with solvents on point F plus Tetrachloroethylene; Do not dry in a tumble dryer; Ironing at low temperature (max 110 °C).</p> <div style="display: flex; justify-content: space-around; align-items: center;"> </div> <div style="text-align: center; margin-top: 5px;"> </div>			
	<table border="0" style="width: 100%;"> <tr> <td style="width: 15%; vertical-align: top;">Item</td> <td style="padding-left: 10px;"> V050-0-00 khaki/black V050-0-01 navy V050-0-02 royal blue/black V050-0-03 clay brown/black V050-0-04 anthracite/black (NEW) V050-0-05 black/black </td> </tr> </table>	Item	V050-0-00 khaki/black V050-0-01 navy V050-0-02 royal blue/black V050-0-03 clay brown/black V050-0-04 anthracite/black (NEW) V050-0-05 black/black	
	Item	V050-0-00 khaki/black V050-0-01 navy V050-0-02 royal blue/black V050-0-03 clay brown/black V050-0-04 anthracite/black (NEW) V050-0-05 black/black		
<table border="0" style="width: 100%;"> <tr> <td style="width: 15%; vertical-align: top;">Standards</td> <td style="padding-left: 10px;"> EN ISO 13688:2013 <div style="float: right; text-align: center;"> </div> </td> </tr> <tr> <td style="vertical-align: top;">sizes</td> <td style="padding-left: 10px;">44 – 64</td> </tr> </table>	Standards	EN ISO 13688:2013 <div style="float: right; text-align: center;"> </div>	sizes	44 – 64
Standards	EN ISO 13688:2013 <div style="float: right; text-align: center;"> </div>			
sizes	44 – 64			



SAFETY TECHNICAL SPECIFICATIONS

<i>Test method</i>	<i>description</i>	<i>Cofra result</i>	<i>minimum requirement / range</i>
Background fabric	EN ISO 1833-1977, SECTION 10 Composition: cotton canvas Weave: Canvas plain 1/1	100% Warp: 8+8 [yarn/cm] Weft: 5+5 [yarn/cm]	
EN ISO 12127:1996	Weight per unit area	257 g/sqm	
EN ISO 105 D01:1993	Colour fastness to dry cleaning	Colour change: 4 – 5	1 - 5
ISO 5077:1994, ISO 6330: 1994	Dimensional change to washes (60°C)	warp: - 2.6 % weft: - 0.5 %	Max ± 3 % Max ± 3 %
ISO 105X12: 2001	Colour fastness to rubbing	dry: 4 - 5 wet: 4 - 5	1 - 5 1 - 5
EN ISO 105 B02: 1993, Method 3	Colour fastness to light	4	1 - 5

	ISO 105-N01:1993	Colour fastness to bleaching	Colour change: 4	1 – 5	
	EN ISO 13934-2: 1999	Tensile strength	warp: 500 N weft: 410 N	400 N 400 N	
	EN ISO 13688:2013 paragraph 4.2 (EN 1413)	The pH's determination from the watery extract	8.9	3,5<PH≤9,5	
	EN ISO 13688:2013 paragraph 4.2 (prEN 14362-1)	Search of the aromatic and carcinogenic amines	Not recording	≤30 ppm	
Reflex 3M™ SCOTCHLITE™ Reflective Material - 8910 Silver Fabric	EN ISO 20471 :2013 6.1	Fotometric requirements of new retroreflective material	IN COMPLIANCE WITH STANDARDS		
	EN ISO 20471 :2013 6.2	Requirements of retroreflective performance after tests for abrasion, flexion, folding at low temperature, thermic variations, washing (25 cycles) and rain influence.	IN COMPLIANCE WITH STANDARDS		
E-care		Composition: PES/CO/MTF	65/33/2%		
		Weight per unit area	215 g/sqm		
		Yarns/cm	warp: 34 weft: 22		
	DIN 53857/1	Tensile strength	warp: 100 daN weft: 65 daN		
	DIN 53892 (3 cicli a 95°C)	Dimensional change to washes	1.5%		
	DIN 54004 (ISO 105B02)	Colour fastness to light	5		
	DIN 54020 (ISO 105E04)	Colour fastness to perspiration	Colour change: 4 staining: 3-4	1 - 5 1 - 5	
	DIN 54021 (ISO 105X12)	Colour fastness to rubbing	dry: 4 wet: 2-3	1 - 5 1 - 5	
	DIN 54024 (ISO 105N01)	Colour fastness to bleaching	4		
	MIL-Standard 285	Attenuation measurements for enclosures, electromagnetic shielding, for electronic test purposes	Reduction of 99,5% of the electromagnetic waves to the frequency of 200 MHz Reduction of 99% of the electromagnetic waves to the frequency of 2000 MHz		